

# bizhub 3601 Black & White A3 multifunctional







MBM Technology Solutions 248.597.1095 www.MBMsolutions.com

Giving Shape to Ideas

Productivity

Reliability, high-speed scanning

and printing, combined with

powerful finishing functions

# **CUSTOMER BENEFITS**



Security Secure network integration, data encryption, hard drive overwrite, and advanced user authentication

# **OPTIONS**



Sustainability

Numerous eco features reduce

energy consumption and costs

Intuitive operability Operate the bizhub like a

smartphone or tablet with fully

customized user interface

OTHERS	4
Document feeder DF-632	
Document feeder DF-714	
Original cover	
Working table WT-506	
<b>10-Key pad</b> KP-102	
Security kit SC-509	Ï
Replacement SSD EM-908	
Keyboard holder KH-102	

LEGEND 

Mandatory option Option

This option can only

4	MEDIAINPUT	
	Intelligent media sensor IM-102	
	<b>1 x Universal tray</b> PC-116	R
,	2 x Universal tray PC-216	Ĺ
	Large capacity tray PC-416	R)
	Large capacity tray PC-417	R)
	Copier desk DK-516	(R)
	Large Capacity tray LU-302	
	Banner tray MK-730	

MEDIA OUTPUT			
Job Separator JS-506	OR Inner Finish FS-533	er	<b>Staple finisher</b> FS-539
	Punch kit PK-519		<b>Relay unit</b> RU-513
			Staple/booklet finisher FS-539SD
			<b>Relay unit</b> RU-513
			<b>Punch kit</b> PK-524

Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive

applications portfolio

 $\Box \Box$ 

 $\Box \Box$ 


Services

Efficient printer fleet

management, including

automatic consumables

delivery, pro-active maintenance and remote setup



# DESCRIPTION

### ENHANCED FEATURES

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint <sup>®</sup> client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender <sup>®</sup> antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

### CONNECTIVITY

EK-608 USB I/F kit	USB keyboard connection
MK-735 Mount kit	Installation kit for ID card reader
ID card reader	Various ID card technologies
AU-102 Biometric authentication	Finger vein scanner
FK-514 Fax board	Super G3 fax, digital fax functionality
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode

#### OTHERS

DF-632 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-714 Document feeder	Dual scan automatic document feeder, capacity 100 originals

OTHERS	
OC-511 Original Cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
KH-102 Keyboard holder	To place USB keyboard

### MEDIA INPUT

IM-102 Intelligent media sensor	Auto detects paper weight and type
PC-116 1x Universal tray	500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" to 11" x 17", 52-256 gsm
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11", 52-256 gsm
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52-256 g/m <sup>2</sup>
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11", 52-256 gsm
MK-730 Banner tray	Multipage banner feeding

## MEDIA OUTPUT

stapling; 3,200 sheets max. output stapling; 20 sheets booklet finisher;
stanling: 20 shoots hooklat finishar:
staphing, zo sneets bookiet infisher,
eets max. output
punching; auto switching
9/SD installation
on of fax output; etc.
stapling, 500 sheets max. output
punching, auto switching

# **TECHNICAL SPECIFICATIONS**

# SYSTEM SPECIFICATIONS

SYSTEM SPECIFICATIONS	
System speed 8.5" x 11"	Up to 36 ppm
System speed 11" x 17"	Up to 18 ppm
Autoduplex speed 8.5" x 11"	Up to 36 ppm
1st page out time 8.5" x 11"	4.6 sec.
Warm-up time	Approx. 12 sec. <sup>1</sup>
Imaging technology	Laser
Toner technology	Simitri <sup>®</sup> HD polymerized toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 100 originals; A6–A3; 35–163 gsm;
(optional)	RADF or Dual scan ADF available
ADF double feed detection	Standard (with dual scan ADF)
Printable paper size	A6-SRA3; banner paper max. 1,200 x 297 mm;
	customized paper sizes
Printable paper weight	52-300 g/m <sup>2</sup>
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500 sheets; 3.5" x 8.5" to 11" x 17"; custom sizes; 52-256 gsm
	1x 500 sheets; 5.5" x 8.5" to 12" x 18"; custom sizes; 52-256 gsm
Paper tray input (optional)	2x 500 sheets; 5.5" x 8.5" to 11" x 17"; 52-256 gsm
	1x 2,500 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Large capacity tray (optional)	1x 3,000 sheets; 8.5" x 11"; custom sizes; 52–256 gsm
Manual bypass	150 sheets; 3.5" x 8.5" to 12" x 18"; Custom sizes; Banner;
	60–300 gsm
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet
Automatic duplexing	5.5" x 8.5" to 12" x 18"; 52–256 gsm

#### SYSTEM SPECIFICATIONS Output capacity Up to 250 sheets / up to 3,300 sheets (standard/max) Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 $g/m^2$ ) Stapling Stapling output capacity Max. 100 sets Tri-fold Max. 3 sheets Max. 30 sets; unlimited (without tray) Tri-fold capacity Booklet Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m<sup>2</sup>) Max. 20 booklets; unlimited (without tray) Booklet output capacity Rec. 33,000 pages; Max.<sup>2</sup> 175,000 pages Duty cycle (monthly) Toner lifetime Black up to 25,000 pages Black up to 245,000/1,000,000 pages (drum/developer) Imaging unit lifetime 110-120 V / 50/60 Hz; Less than 1.50 kW Power consumption System dimension (W x D x H) 24.2" x 27" x 31" (without options) System weight Approx. 187 lbs. (without options) PRINTER SPECIFICATIONS Print resolution 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi Page description language PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); **Operating systems** Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux Printer fonts 80 PCL Latin; 137 PostScript 3 Emulation Latin Mobile printing Konica Minolta Print Service (Android); Konica Minolta Mobile Print (iOS/Android); AirPrint (iOS), Mopria (Android)

optional: WiFi Direct

#### bizhub 360i Datasheet

### SCANNER SPECIFICATIONS

4

Scan speed	Up to 100 ipm in simplex (mono)	
	Up to 200 ipm in duplex (mono)	
Scan resolution	Up to 600 x 600 dpi	
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);	
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-	
	to-DPWS; Scan-to-URL; TWAIN scan	
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact	
	XPS; PPTX	
	Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/	
	PPTX/XLSX	
Scan destinations	2,000 destinations + 100 groups; LDAP support	

#### COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming

### FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

### USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL3 and TLS1.0/1.1/1.2 network communica
	tion; IPsec support; IEEE 802.1x support; User authentication;
	Authentication log; Secure print; Kerberos; Hard drive overwrite;
	Hard drive data encryption (AES 256); Confidential fax; Print user
	data encryption
	optional: Antivirus realtime scanning (Bitdefender®); Copy
	protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

<sup>1</sup> Warm-up time may vary depending on the operating environment and usage

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to letter-size paper of 80 gsm weight.
   The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
  particular page size (6% coverage of letter).. The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to \_ change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free. \_
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



**MBM** Technology Solutions

375 Robbins Drive, Troy, MI 48083 248.597.1095

www.MBMsolutions.com

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com



Item #: 360iSS 9/2020-Z