



Black & White A3 multifunctional











seamless technology integration

MBM Technology Solutions 248.597.1095 www.MBMsolutions.com

Giving Shape to Ideas

CUSTOMER BENEFITS



Security

Secure network integration, data encryption, hard drive overwrite and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



PDF enhancements

OCR text recognition

Barcode fonts LK-106

Unicode fonts

OCR A and B fonts

Document converter pack

ThinPrint® client

Antivirus LK-116

FOIP IP Fax (T.38)



2 CONNECTIVITY Fax board

Wireless LAN UK-221

USB I/F kit USB I/F kit

Biometric authentication

х2

ID card reader

Mount kit MK-735

3 OTHERS

Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

1x Universal tray PC-116 2x Universal tray

Large capacity tray PC-417

Large capacity tray

Large capacity tray LU-207

Banner tray

5 MEDIA OUTPUT

Output tray OT-513

Attachment kit MK-607

Staple finisher FS-539

ınch kit for FS-539/SD

Staple finisher FS-540

Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

OR)

Post inserter for FS-540/SD PI-507 Job separator for FS-540/SD OR

Z-fold unit for FS-540/SD

LEGEND

Mandatory option

This option can only be installed with the respective option

Option

above it

FINISHING FUNCTIONALITIES















Half-fold



















stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

SC-509 Security kit

MEDIA INPUT

EM-908 Replacement SSD

KH-102 Keyboard holder

PC-116 1x Universal tray

IM-102 Intelligent media sensor

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint® client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all
	incoming and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit
CONNECTIVITY	
CONNECTIVITY	
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-514 Fax board	Super G3 fax, digital fax functionality Wireless LAN and wireless LAN Access Point Mode
FK-514 Fax board UK-221 Wireless LAN	
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit	Wireless LAN and wireless LAN Access Point Mode
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit AU-102 Biometric authentication	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection USB keyboard connection; Bluetooth
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit AU-102 Biometric authentication ID card reader	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection USB keyboard connection; Bluetooth Finger vein scanner
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit AU-102 Biometric authentication ID card reader	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection USB keyboard connection; Bluetooth Finger vein scanner Various ID card technologies
CONNECTIVITY FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit AU-102 Biometric authentication ID card reader MK-735 Mount kit	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection USB keyboard connection; Bluetooth Finger vein scanner Various ID card technologies
FK-514 Fax board UK-221 Wireless LAN EK-608 USB I/F kit EK-609 USB I/F kit AU-102 Biometric authentication ID card reader MK-735 Mount kit	Wireless LAN and wireless LAN Access Point Mode USB keyboard connection USB keyboard connection; Bluetooth Finger vein scanner Various ID card technologies

Copy guard function

To place USB keyboard

1 TB SSD to increase storage space

Auto detects paper weight and type

500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m 2

PC-216 2x Universal tray	2x 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ²
PC-416 Large capacity tray	2,500 sheets, 8.5" x 11" / 52–256 g/m ²
PC-417 Large capacity tray	1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m ²
LU-302 Large capacity tray	3,000 sheets, 8.5" x 11" / 52–256 g/m ²
LU-207 Large capacity tray	2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m²
MK-730 Banner tray	Multipage banner feeding
MEDIA OUTPUT	
OT-513 Output tray	Output tray used instead of finisher
JS-508 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
MK-607 Attachment kit	For FS-533 installation
PK-519 Punch kit for FS-533	2/3-hole punching, auto switching
FS-539 Staple finisher	50-sheet stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50-sheet stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/3-hole punching; auto switching
FS-540 Staple finisher	100 sheets stapling; 3,200 sheets max. output
FS-540SD Booklet finisher	100 sheets stapling; 20 sheets booklet finisher;
	2,700 sheets max. output
PK-526 Punch kit for FS-540/SD	2/3-hole punching; auto switching
RU-513 Relay unit	For FS-539/SD or FS-540/SD installation
JS-602 Job separator for FS-540/SD	Separation of fax output; etc.
PI-507 Post inserter for FS-540/SD	Cover insertion; post finishing
ZU-609 Z-fold unit for FS-540/SD	Z-fold for 11" x 17" prints

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS Up to 55 ppm System speed 8.5" x11" System speed 11" x 17" Up to 27 ppm Autoduplex speed 8.5" x 11" Up to 55 ppm 1st page out time 8.5" x 11" 3.3 sec. Warm-up time Approx. 14 sec.1 Imaging technology Toner technology Simitri® HD polymerized toner Panel size/resolution 10.1" / 1024 x 600 8,192 MB (standard/max) System memory System hard drive 256 GB SSD (standard) / 1 TB SSD (optional) 10/100/1,000-Base-T Ethernet; Interface USB 2.0; Wi-Fi 802.11 b/g/n/ac (optional) Network protocols TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S) Automatic document feeder Up to 300 originals / 5.5" x 8.5" – 11" x 17" / $35-210~g/m^2$ / Dual scan ADF ADF double feed detection Standard Printable paper size 3.5" x 5.5" – 12" x 18" / customized paper sizes / banner paper max. 47.2" x 11.7" $52-300 \text{ g/m}^2$ Printable paper weight Paper input capacity 1,150 sheets / 6,650 sheets (standard/max) Paper tray input (standard) $1 \times 500 / 3.5$ " x 5.8" – 11" x 17" / custom sizes / 52-256 g/m² $1\,x\,500\,/\,5.5"\,x\,8.5"$ – $12"\,x\,18"\,/\,$ custom sizes $/\,52$ – $256\,g/m^2$ $1 \times 500 / 5.5$ " $\times 8.5$ " – 11" $\times 17$ " / 52– 256 g/m^2 Paper tray input (optional) $2 \times 500 / 5.5$ " x 8.5" – 11" x 17"/ 52– $256 \, g/m^2$ $1\,x\,2,500\,/\,8.5"\,x\,11"\,/52-256\,g/m^2$

52-256 g/m²

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11" /

Large capacity tray (optional)	1 x 3,000 / 8.5" x 11" / 52-256 g/m ²
	1 x 2,500/ 8.5" x 11" – 12" x 18" / custom sizes /
	52-256 g/m ²
Manual bypass	150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes /
	banner / 60–300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold;
	Letter-fold; Booklet; Post insertion; Z-fold
Automatic duplexing	4.1" x 5.5" – 12" x 18" / 52–256 g/m²
Output capacity	Up to 250 sheets / up to 3,300 sheets (standard/max)
Stapling	Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m²)
Stapling output capacity	Max. 200 sets
Letter fold	Max. 3 sheets
Letter fold capacity	Max. 50 sets; unlimited (without tray)
Booklet	Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m²)
Booklet output capacity	Max. 35 booklets; unlimited (without tray)
Duty cycle (monthly)	Rec. 50,000 pages; Max. ² 200,000 pages
Toner lifetime	Black up to 24,000 pages
Imaging unit lifetime	Black up to 260,000/1,000,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 2.00 kW
System dimension (W x D x H)	24.2" x 27.1" x 37.8" (without options)
System weight	Approx. 220 lb (without options)

SYSTEM SPECIFICATIONS

bizhub 550i Datasheet

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS); Mopria (Android)
	optional: WiFi Direct

SCANNER SPECIFICATIONS

00/11/11/21/01/2011/0/11/0/	
Scan speed	Up to 140 ipm in simplex (mono)
	Up to 280 ipm in duplex (mono)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

001 121(01 2011 1011)	
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. 11" x 17"
Magnification	25-400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

Super G3 (optional)	
Analog; i-Fax; Color i-Fax; IP-Fax	
Up to 600 x 600 dpi	
MH; MR; MMR; JBIG	
Up to 33.6 Kbps	
2,000 single + 100 groups	

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation);
	IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard drive overwrite; Hard drive data encryption (AES 256);
	Confidential fax; Print user data encryption
	optional: Antivirus realtime scanning (Bitdefender®);
	Copy protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

- All specifications refer to 8.5" x 11"-size paper of 80 g/m 2 quality.
- $\ \ \, \text{The support and availability of the listed specifications and functionalities varies depending on operating systems,}$ applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a $particular\ page\ size\ (5\%\ coverage\ of\ 8.5''\ x\ 11'').\ The\ actual\ life\ of\ each\ consumable\ will\ vary\ depending\ on\ use\ and$ other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.























For complete information on Konica Minolta products and solutions, please visit: CountOnKonicaMinolta.com

© 2020 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission



MBM Technology Solutions 375 Robbins Drive, Troy, MI 48083

248.597.1095 www.MBMsolutions.com

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. 100 Williams Drive, Ramsey, New Jersey 07446

CountOnKonicaMinolta.com









¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed